

subject.

Radiation Survey of AECL Model GC220 Gamma-Cell SN 136 Case 48100-2

te Mar

March 7, 1985

from

S. S. Voris MH 77622 1F-101F X4645

A radiation survey was conducted on 3/7/85 of the AECL Model GC220 EX U Gamma-Cell located in The activity of the Co-60 source as of 3/7/85 was 10.98 MCi. Access to the Gamma-Cell, as indicated in the attached drawing, is controlled by

CX.4

Results of the survey, with reference to the attached drawing, are as follows:

Location A 4.0 mR/hr maximum at 6 inches from the front surface at a height of 32 inches with elevator in up position. 5.5 mR/hr with elevator down.

Location B 2.5 mR/hr maximum at 6 inches from the left side surface at a height of 32 inches with elevator up. 3.6 mR/hr with elevator down.

Location C 3.6 mR/hr maximum at 6 inches from the back surface at a height of 32 inches with elevator up. 5.0 mR/hr with elevator down.

Location D 2.3 mR/hr maximum at 6 inches from right side surface at a height of 32 inches with elevator up. 3.6 mR/hr with elevator down.

A measurement indicating 6 mR/hr was made at 3 inches from the bottom of the source container. The radiation level inside the sample chamber in the up position was 24 mR/hr. With the sample chamber shield doors closed a reading at the top surface was 1.4 mR/hr. A maximum reading at the top of the elevator in the down position showed 4.6 mR/hr. A reading of about 80 mR/hr was indicated at the top of the elevator during its up-down cycle for an exposure period of about 2 seconds.

Additional measurements were made in the ajoining room No radiation above normal background levels of 0.01 to 0.02 mR/hr were detected. A survey of the top of the block wall adjacent to the Gamma-Cell showed a level of 0.02 mR/hr. The levels outside the block wall were at normal background with the exception of the opening to the Gamma-Cell where a level of 0.9 mR/hr was detected. The survey was conducted with a Health Physics Instrument Model 1010 Ion Chamber meter last calibrated 11/29/84.

in accordance with the Freedom of Information Act, exemptions

EDIA- 3003-010A

A routine quarterly leak test was made of the radioactive source by wiping the outside of the sample chamber. The wipe sample, measured with a Tennelec 5100 series low background gas flow proportional counting system, indicated a contamination level of $<1.33\times10^{-6}~\mu$ Ci. The Bell Laboratories action level is $5.00\times10^{-5}~\mu$ Ci of removable contamination for beta-gamma sealed sources. The source must be taken out of service and reported to the Nuclear Regulatory Commission if the leak test shows a contamination level of $5 \mathrm{x} 10^{-3}~\mu \, \text{Ci}$ or greater.

MH-77622-SSV-md

Radiological Safety Officer

Att.

Copy to

J. W. Mitchell

J. W. Rodgers

W. Vroom

M. M. Weiss

G. M. Wilkening

5----

EX.4

SCALE

1/4 INCH = 1 FOOT